

Giving Shape to Ideas









bizhub C554e

Ideal for high-speed color output and fast scanning to multiple destinations, the bizhub C554e can power up your workflow with 55 ppm output in both color and B&W, enhanced touch-screen convenience and multiple finishing options for creating high-impact color documents in-house.

System Overview

| System overview | |
|--|--|
| System memory | 2,048 MB |
| System hard disk | 250 GB |
| Interface | 10-BASE-T/100-BASE-TX/1,000-BASE-T Ethernet, USB 2.0 |
| Network protocols | TCP/IP (IPv4/IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS |
| Frame types | Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP |
| Dual scan | Up to 100 originals / 5.5" x 8.5" to 11" x 17" / 35-163 gsm |
| document feeder | |
| Printable paper size | Scanning/Copying: up to 11" x 17" |
| | Printing: up to 11" x 17" full bleed on 12" x 18" paper |
| | Custom paper sizes Banner paper max: 11.75" x 47.25" |
| Printable paper weight | 52-300 gsm |
| | - |
| Paper input capacity Tray 1 | Standard: 1,150 sheets / Max.: 6,650 sheets 500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm |
| Tray 2 | 500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm |
| Tray 3 (optional) | 500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm |
| Tray 4 (optional) | 2 x 500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm |
| | <u> </u> |
| Large capacity tray PC-410 (optional) | 2,500 sheets / 8.5" x 11" / 52-256 gsm |
| Large capacity tray LU-301 (optional) | 3,000 sheets / 8.5" x 11" / 52-256 gsm |
| Large capacity tray LU-204 (optional) | 2,500 sheets / 8.5" x 11" to 12" x 18" / 52-256 gsm |
| Manual bypass | 150 sheets / 4" x 6" to 12" x 18" / custom paper sizes / 50-300 gsm |
| Automatic duplexing | 5.5" x 8.5" to 12" x 18" / 52-256 gsm |
| Finishing modes | Offset, group, sort, punch, post insertion, z-fold, half-fold, tri-fold, booklet |
| Output capacity | Max. with finisher: 3.300 sheets |
| output oupdoing | Max. without finisher: 250 sheets |
| Stapling (optional) | Max.: 100 sheets or 94 sheets + 2 cover sheets (up to 209 gsm) |
| Stapling output capacity | Max.: 1000 sheets |
| Tri-fold | Up to 3 sheets |
| Tri-fold capacity | Max.: 30 sheets (tray), unlimited |
| Booklet | Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm) |
| Booklet output capacity | Max.: 100 sheets (tray), unlimited |
| Copy/print volume | Max.: 200,000 pages/month ¹ |
| Toner lifetime | Black: 27,000 pages / CMY: 26,000 pages |
| Imaging unit lifetime | Black: 135,000 pages / 590,000 pages (Drum / Developer) |
| 33 | CMY: 95,000 pages |
| Power consumption | 120 V / 50/60 Hz, less than 1.92 kW (system) |
| System dimensions | 24.2" x 27" x 36.3" (W x D x H) |
| System weight | Approx. 220.5 lb |
| | |

| Caniar | Cnoc | ifion | Hiono |
|--------|------|--------|-------|
| Copier | SUUL | illica | นบทร |

| Copying process | Electrostatic laser copy, tandem, indirect | |
|----------------------------------|--|--|
| Toner system | Simitri® HD Polymerized Toner | |
| Print speed (8.5" x 11") | B&W / Color: up to 55 ppm (Portrait) | |
| Print speed (11" x 17") | B&W / Color: up to 27 ppm (Portrait) | |
| Autoduplex speed (8.5" x 11") | B&W / Color: up to 55 ppm (Portrait) | |
| 1st copy out time | B&W: 4.1 sec. / Color: 4.6 sec. | |
| Warm-up time | Approx. 22 sec. ² | |
| Copy resolution | 600 x 600 dpi | |
| Gradations | 256 gradations | |
| Multi-copy | 1-9,999 | |
| Original format | Up to 11" x 17" | |
| Magnification | 25-400% in 0.1% steps, auto zooming | |
| Copy functions | Chapter, cover and page insertion, proof copy (print and screen), adjustment test print, digital art functions, job setting memory, poster mode, image repeat, overlay (optional), stamping, copy protection | |

Printer Specifications

| Print resolution | 1,800 x 600 dpi, 1,200 x 1,200 dpi | |
|-------------------|---|--|
| PDL | PCL6 (XL 3.0), PCL5c, PostScript 3 (ver. 3016), XPS | |
| Operating systems | Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 ³ / 2012 ³ Macintosh OS X 10.2.8 or later UNIX / Linux / Citrix | |
| Printer fonts | 80 PCL Latin, 137 PostScript 3 | |
| Print functions | Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print | |

Printer Specifications (Optional)

| Print controller | Embedded Fiery IC-414 |
|-------------------|---|
| Memory/HDD | 2 GB / 160 GB |
| PDL | PostScript 3 (ver. 3019) PCL 6/5c |
| Operating systems | Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 ³ / 2012 ³ Macintosh DS X 10 2 8 or later |

Scanner Specifications

| Scan speed | B&W / Color: up to 160 ipm |
|-------------------|---|
| Scan resolution | Max.: 600 x 600 dpi |
| Scan modes | Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan |
| File formats | JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/XLSX (optional) |
| Scan destinations | 2,100 (shared with fax), LDAP support |
| Scan functions | Annotation (text/time/date) for PDF, up to 400 job programs, realtime scan preview |

Fax Specifications

| Fax | Super G3 (optional) | |
|--------------|--|--|
| Transmission | Analog, i-Fax, Color i-Fax, IP-fax | |
| Resolution | Max.: 600 x 600 dpi (ultra-fine) | |
| Compression | MH, MR, MMR, JBIG | |
| Modem | Up to 33.6 Kbps | |
| Destinations | 2,100 (single + group) | |
| Functions | Polling, time shift, PC-fax, receipt to confidential box, receipt to | |

User Box Specifications

| Storable documents | Max.: 3,000 documents or 10,000 pages | |
|------------------------|---|--|
| Type of user boxes | Public | |
| | Personal (with password or authentication) | |
| | Group (with authentication) | |
| Type of system boxes | Secure print, encrypted PDF, fax receipt, fax polling, annotation | |
| User box functionality | Reprint, combination, download, sending (Email/FTP/SMB and fax), | |
| | copy box-to-box | |

| 4 . | |
|--------|----------|
| Syctem | Features |

| Security | ISO 15408 EAL |
|-----------------------|--|
| | IEEE 2600.1 |
| | IP filtering and port blocking |
| | SSL2, SSL3 and TSL1.0 network communication |
| | IPsec support |
| | IEEE 802.1x support |
| | User authentication |
| | Authentication log |
| | Secure print |
| | Hard disk overwrite (8 standard types) |
| | Hard disk data encryption (AES 128) |
| | Memory data auto deletion |
| | Confidential fax receipt, |
| | Print user data encryption |
| | Copy protection (Copy Guard, Password Copy) optional |
| Accounting | Up to 1,000 user accounts |
| | Active Directory support |
| | (user name + password + Email + SMB folder) |
| | User function access definition |
| | Optional Biometric authentication (finger vein scanner) |
| | Optional ID card authentication (ID card reader) |
| Software | PageScope Net Care Device Manager |
| | PageScope Data Administrator |
| | PageScope Box Operator |
| | PageScope Direct Print |
| | Print Status Notifier |
| | Driver Packaging Utility |
| | Log Management Utility |
| 1 Maximum monthly dut | y cycle describes the maximum number of nages a device can output on a monthly basis |

[|] Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis.
| This specification is a guidline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs 2 Warm-up time may vary depending on the operating environment and usage 3 Supports x64 only

| Components and Options | 5 |
|--|--|
| AU-102 Biometric | Finger vein scanner |
| authentication | LICD transpared composition |
| EK-606 USB I/F kit | USB keyboard connection |
| EK-607 USB I/F kit | USB keyboard connection, Bluetooth |
| DK-510 Copier desk | Provides storage space for print media and other materials |
| FK-508 Fax board | Super G3 fax, digital fax functionality, lines 3 & 4 support |
| FK-511 Fax board | Super G3 fax, digital fax functionality |
| FS-533 Staple finisher | 50-sheet stapling, 500 sheets max. output |
| FS-534 Staple finisher FS-534 + SD-511 | 50-sheet stapling, 3,300 sheets max. output 50-sheet staple finisher, 20-sheet booklet finisher, |
| Booklet finisher | 3,300 sheets max. output |
| FS-535 Staple finisher | 100-sheet stapling, 3,200 sheets max. output |
| IC-414 Fiery controller | Professional color print controller |
| ID card reader | Various ID card technologies |
| JS-506 Job separator | Separation for fax output, etc. |
| JS-602 Job separator | Separation for fax output, etc. |
| for FS-535 | ocparation for tax output, etc. |
| KH-102 | To place USB keyboard |
| Keyboard holder | |
| KP-101 10-Key pad | For use instead of touchscreen |
| LK-101 v3 | Web browser |
| Web browser | |
| LK-102 v3 | PDF/A, PDF encryption, digital signature |
| PDF enhancements | |
| LK-104 v3 | Provides voice guidance functions |
| Voice guidance | Casashahla DDF |
| LK-105 v3 OCR text recognition | Searchable PDF |
| LK-106 | Supports native barcode printing |
| Barcode fonts | Supports flative barcode printing |
| LK-107 | Supports native Unicode printing |
| Unicode fonts | Capports Hauve Officed printing |
| LK-108 | Supports native OCR A and B font printing |
| OCR A and B fonts | |
| LK-110 Enhanced | Generates various file formats incl. DOCX, XLSX and combines |
| image support | LK-102 (encrypted PDF) + LK-105 (searchable PDF/OCR functionality) |
| LK-111 | Print data compression for reduced network impact |
| ThinPrint® Client | 0 E" v 11" to 10" v 10" 0 E00 abouts E0 050 |
| LU-204 Large capacity tray | 8.5" x 11" to 12" x 18", 2,500 sheets, 52-256 gsm |
| LU-301 | 8.5" x 11", 3,000 sheets, 52-256 gsm |
| Large capacity tray | J.O. A. I. , 0,000 dilotto, 02-200 yolli |
| MK-728 Mount kit | Installation kit for FK-508 fax board |
| MK-735 Mount kit | Installation kit for ID card reader |
| OT-506 Output tray | Output tray used instead of finisher |
| PC-110 | 5.5" x 8.5" to 11" x 17", 500 sheets, 52-256 gsm |
| Universal tray (x1) | |
| PC-210 | 5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52-256 gsm |
| Universal tray (x2) | |
| PC-410 Large | 8.5" x 11", 2,500 sheets, 52-256 gsm |
| capacity tray | 0 |
| PI-505 Post inserter | Cover insertion, post finishing |
| for FS-535 PK-519 Punch kit | 2/3-hole punching, autoswitching |
| for FS-533 | 270-now punioning, autoswitching |
| PK-520 Punch kit | 2/3-hole punching, autoswitching |
| for FS-534 | |
| PK-521 Punch kit | 2/3-hole punching, autoswitching |
| for FS-535 | |
| SC-508 Security kit | Copy Guard function (2x required) |
| SD-512 Saddle kit for | Booklet finishing, half-fold, tri-fold |
| FS-535 | |
| UK-204 | Memory extension for i-Options |
| i-Option memory | |
| | |
| | Fiery controller interface card |
| | Authorition device placement |
| | · |
| | Z-TOTATION TO X T7 PRIMES, Z/S HOTE PUNCTIMES |
| PK-521 Punch kit for FS-535 SC-508 Security kit SD-512 Saddle kit for FS-535 UK-204 | Copy Guard function (2x required) Booklet finishing, half-fold, tri-fold |



KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446





