

As part of a total digital document solution or a stand-alone MFP, the bizhub 552 will prove its value in speeding your output and streamlining your workflow. Its 55 ppm print/copy speed helps you keep pace with rising document traffic. Color scanning at up to 78 originals per minute allows you to digitize and distribute information more quickly. Compact cabinetry and sleek dark styling fits in anywhere – corporate and legal offices, educational institutions, healthcare facilities, government agencies and service bureaus. Even light production environments will benefit from sophisticated finishing options, high-yield Simitri[®] HD Toner with Biomass, powerful Pagescope[®] software, bizhub Extended Solution Technology (bEST) for seamless integration with 3rd-party programs, and state-of-the-art security options. With the bizhub 552, you'll be working smarter – and saving time and money.

B&W cost-efficiency, color scanning productivity.



printer/copier/scanner/fax





Eco Vision 2050 is Konica Minolta's commitment to protect the environment – saving energy, preserving resources, promoting recycling and reducing CO₂ emissions to help sustain the environment for generations to come. Please visit our website to learn more about our environmental initiatives and our exclusive Clean Planet Program. www.cleanplanetus.com

bizhub 552

- HIGH-SPEED PRINT/COPY OUTPUT AT UP TO 55 PPM
- COLOR SCANNING TO MULTIPLE DESTINATIONS AT UP TO 78 OPM
- SCAN TO USER BOX, SCAN-TO-ME, SCAN-TO-HOME
- SCAN-TO-EMAIL AND FTP, SCAN TO/FROM USB THUMB DRIVE
- 8.5" COLOR TOUCH-SCREEN WITH THUMBNAIL DOCUMENT PREVIEW
- EMPERON® PRINT SYSTEM, PCL6/PS3 EMULATION, NATIVE XPS
- STANDARD 250 GB HDD FOR HIGH-CAPACITY STORAGE
- 6,650-SHEET MAXIMUM PAPER CAPACITY IN WEIGHTS UP TO 300 GSM
- FINISHING OPTIONS FOR BOOKLETS, STAPLING, 2/3-HOLE PUNCH
- i-OPTION™ KITS: SEARCHABLE PDF, WEB ACCESS, PDF ENCRYPTION
- ENHANCED SECURITY FUNCTIONS TO SAFEGUARD INFORMATION
- HID PROXIMITY CARD AND BIOMETRIC AUTHENTICATION OPTIONS
- OPTIONAL SUPER G3 FAX; STANDARD INTERNET FAX, IP ADDRESS FAX
- PAGESCOPE® NETWORKING, PAGESCOPE ENTERPRISE SUITE
- GREEN TECHNOLOGIES TO SAVE ENERGY, REDUCE WASTE

COUNT ON KONICA MINOLTA

bizhub 552 printer/copier/scanner/fax



COUNT ON KONICA MINOLTA

| SPECIFICATIONS Type/Process/Toner Type | |
|---|---|
| IVDE/PIOCESS/ IOHEL IVDE | Printer/Copier/Full-Color Scanner with Stationary Platen; Tandem Process; Simitri® HD Toner with Biomass |
| Print/Copy Speed | B&W: 55 ppm (letter, portrait) |
| Monthly Duty Cycle (Pages) | 150,000 |
| СОРУ | |
| Warm-up Time/First Copy Time | Less than 30 seconds/Less than 4.3 seconds |
| Copy Resolution/Quantity | 1800 dpi equivalent x 600 dpi/1-9,999 |
| Magnification | Zoom range: 25% - 400%, 0.1% increments, Preset reduction: 79%, 73%, 65%, 50%, Preset enlargement: 121%, 129%, 155%, 200% |
| Copy Exposure Modes | Text (legible text), Text/Photo (clear text and halftones), Photo (optimized for gradations), Dot Matrix (dot matrix or pencil originals), Copied Paper |
| PRINT – Emperon Print System with bizhub Extended Sol | ution Technology / Open API |
| Processor/Memory/Hard Disk Drive | 1 GHz (MPC8533)/2 GB RAM (shared copier memory)/250 GB (shared copier HDD) |
| Print Resolution/Gradation | 1800 dpi equivalent x 600 dpi/256 shades per pixel |
| Interface | 10 Base-T/100 Base-TX/1000 Base-T, USB 1.1 Host Port, USB 2.0 |
| Page Description Language/Fonts | PCL5e/c, PCL6 (XL v.3.0) Emulation, PS3 (v.3016) Emulation, XPS v.2.1.4.0 (XML Paper Specification)/PCL: 80 fonts, PostScript 3 Emulation: 137 fonts |
| Print Drivers | PCL6: Windows 2000 Professional, Windows XP Home/Professional (x32, x64), Windows Vista (x32, x64), Windows 7 (x32, x64), Windows Server 2003 (x32, x64), |
| | Windows Server 2003 R2, Windows Server 2008 (x32, x64), Windows Server 2008 R2; PS3: Windows 2000 Professional, Windows XP Home/Professional (x32, x64), |
| | Windows Vista (x32, x64), Windows 7 (x32, x64), Windows Server 2003 (x32, x64), Windows Server 2003 R2, Windows Server 2008 (x32, x64), Windows Server 2008 R2; |
| | - Universal PS3 and PCL: Windows 2000, Windows XP, Windows Vista, Windows 7 (x32, x64), Windows Server 2003, Windows Server 2008 (x32, x64); XPS: Windows Vista (x32, x64) |
| | Windows 7 (x32, x64), Windows Server 2008 (x32, x64), Windows Server 2008 R2; Mac: OS 9.2 (PPD file), OS X 10.2, 10.3, 10.4; Intel-based: 10.4 (print driver), 10.5, 10.6 |
| Protocols | TCP/IP, IPX/SPX, AppleTalk (EtherTalk), LPR, SMB, LPD, Netware (4.x, 5, 6), Pserver, Nprinter, NDPS, IPP 1.1, SMTP, POP3, LDAP, SSL/TLS, SNMP, HTTP/HTTPS, IPv4, IPv6, DPWS (WSD) |
| COPY/PRINT FUNCTIONS | |
| Copy/Print | Account Track (1,000 accounts), Administration Mode, Auto Duplex, Auto Trapping, Auto Tray Switching, Bi-Directional Communication, Black Over Print, Card Shot, |
| | Copy Guard, Copy Modes (Simplex/Duplex, 2-in-1, 4-in-1, 8-in-1, Book, Booklet, Booklet + Bind), Cover Mode, Creative Functions (Mirror Image, XY Zoom, Image Center, |
| | Image Adjustment, Neg./Pos. Reverse, Image Repeat), Encrypted Network Password Printing, Energy Save Mode, Enlarge Display, Erase Mode (Border, Frame, Edge), |
| | Finishing (Group, Sort, Staple, Punch, Half-Fold, Center Staple and Fold, Tri-Fold), Form Overlay, Glossy Mode, HDD Encryption, HDD Job Overwrite, HDD Sanitizing, |
| | Image Adjustments (Contrast, Copy Density, Sharpness), Image Preview (Job Finishing, Image Display, Engine Configuration Display), Interrupt, Job List, Job Reserve, Job Skip, |
| | LDAP, Mixplex, Mix-Media, MyTab, Non-Image Area Erase, OHP Interleaving, Password Copy, Program/Recall Jobs, Paper Type Selection (Normal, Thick 1/1+, Thick 2, Thick 3, |
| | Thick 4), Print Modes (Simplex/Duplex, 2-in-1, 4-in-1, 6-in-1, 9-in-1, 16-in-1, Booklet, Booklet + Bind), Print from USB, Proof Copy, Secure Printing, Separate Scan, |
| | Text Enhancement, User Authentication (Up to 20 Authentication Servers) (Synchronize w/Account Track), User Box Function, Utility (Meter Count, Environment Setting, |
| | Default Setting, One-Touch Setting, Check Consumables Life), Watermark, Zoom Selection |
| SCAN | |
| Scan Speed/Scan Resolution | Full Color: 78 opm (@ 300 dpi, letter), 55 opm (@ 600 dpi, letter), B&W: 78 opm (@ 300 dpi, letter), 65 opm (@ 600 dpi, letter) / 200 dpi, 300 dpi, 400 dpi, 600 dpi |
| Scan File Formats | TIFF, PDF, Compact PDF, JPEG, XPS, Compact XPS |
| Scan Functions | Scan-to-Email, Scan-to-FTP, Scan-to-HDD (Scan-to-User Box), Scan-to-Me/Scan-to-Home, Scan-to-SMB (Scan-to-Desktop), Scan-to-WebDAV, Network TWAIN, |
| | WS-Scan, Color Internet Fax, Color Modes & Functions (Auto Color/Full Color, Grayscale, Black Mode) |
| SA-502 Scan Accelerator Kit | Accelerates scan conversion process |
| • FAX | |
| FK-502 Fax Board | Super G3 compatibility, MH, MR, MMR, JBIG data compression, 33.6 kbps modem speed |
| MK-720 Fax Mount Kit | Required for FK-502 installation |
| | Less than 3 seconds/page (JBIG, standard resolution) |
| Fax Line/Mode | PSTN, PBX, G3 |
| Fax Exposure Mode | Text, Text/Photo, Photo, Dot Matrix |
| | |
| Fax Features | Autodialing (2,000 one-touches), Auto Memory Reception, Auto Reduction Printing, Broadcasting (maximum 605 locations), Bulletin Board, Duplex Transmission/Reception, |
| | Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas |
| | Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas Transmission, Password Transmission/Reception, PC-Fax, Polling Transmission/Reception, Priority Transmission, Print Setting or Overnight Reception, Program Dialing (400 programs) |
| | Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas |
| • Fax Features | Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas Transmission, Password Transmission/Reception, PC-Fax, Polling Transmission/Reception, Priority Transmission, Print Setting or Overnight Reception, Program Dialing (400 programs, Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing |
| • Fax Features • PAPER INPUT Reversing Auto Document Feeder | Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas Transmission, Password Transmission/Reception, PC-Fax, Polling Transmission/Reception, Priority Transmission, Print Setting or Overnight Reception, Program Dialing (400 programs Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing 78 opm, Capacity: 100 Sheets, Paper Size: 5.5" x 8.5" to 11" x 17", Paper Weight: Single-sided: 9.25 lb. to 55.75 lb. bond, Double Sided or mixed: 13.25 lb. to 34 lb. bond |
| • Fax Features PAPER INPUT Reversing Auto Document Feeder Original Size | Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas Transmission, Password Transmission/Reception, PC-Fax, Polling Transmission/Reception, Priority Transmission, Print Setting or Overnight Reception, Program Dialing (400 programs), Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing 78 opm, Capacity: 100 Sheets, Paper Size: 5.5" x 8.5" to 11" x 17", Paper Weight: Single-sided: 9.25 lb. to 55.75 lb. bond, Double Sided or mixed: 13.25 lb. to 34 lb. bond Up to 11" x 17" |
| • Fax Features • PAPER INPUT Reversing Auto Document Feeder Original Size Tray 1 & Tray 2 | Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas Transmission, Password Transmission/Reception, PC-Fax, Polling Transmission/Reception, Priority Transmission, Print Setting or Overnight Reception, Program Dialing (400 programs) Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing 78 opm, Capacity: 100 Sheets, Paper Size: 5.5" x 8.5" to 11" x 17", Paper Weight: Single-sided: 9.25 lb. to 55.75 lb. bond, Double Sided or mixed: 13.25 lb. to 34 lb. bond Up to 11" x 17" 500-sheet (universal cassette)/5.5" x 8.5" to 12" x 18"/17 lb. bond to 140 lb. index |
| • Fax Features PAPER INPUT Reversing Auto Document Feeder Original Size Tray 1 & Tray 2 Tray 3 | Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas Transmission, Password Transmission/Reception, PC-Fax, Polling Transmission/Reception, Priority Transmission, Print Setting or Overnight Reception, Program Dialing (400 programs) Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing 78 opm, Capacity: 100 Sheets, Paper Size: 5.5" x 8.5" to 11" x 17", Paper Weight: Single-sided: 9.25 lb. to 55.75 lb. bond, Double Sided or mixed: 13.25 lb. to 34 lb. bond Up to 11" x 17" 500-sheet (universal cassette)/8.5" x 8.5" to 12" x 18"/17 lb. bond to 140 lb. index 1,500-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index |
| • Fax Features PAPER INPUT Reversing Auto Document Feeder Original Size Tray 1 & Tray 2 Tray 3 Tray 4 | Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas Transmission, Password Transmission/Reception, PC-Fax, Polling Transmission/Reception, Priority Transmission, Print Setting or Overnight Reception, Program Dialing (400 programs) Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing 78 opm, Capacity: 100 Sheets, Paper Size: 5.5" x 8.5" to 11" x 17", Paper Weight: Single-sided: 9.25 lb. to 55.75 lb. bond, Double Sided or mixed: 13.25 lb. to 34 lb. bond Up to 11" x 17" 500-sheet (universal cassette)/5.5" x 8.5" to 12" x 18"/17 lb. bond to 140 lb. index 1,500-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index |
| • Fax Features PAPER INPUT Reversing Auto Document Feeder Original Size Tray 1 & Tray 2 Tray 3 Tray 4 Bypass Tray | Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas Transmission, Password Transmission/Reception, PC-Fax, Polling Transmission/Reception, Priority Transmission, Print Setting or Overnight Reception, Program Dialing (400 programs, Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing 78 opm, Capacity: 100 Sheets, Paper Size: 5.5" x 8.5" to 11" x 17", Paper Weight: Single-sided: 9.25 lb. to 55.75 lb. bond, Double Sided or mixed: 13.25 lb. to 34 lb. bond Up to 11" x 17" 500-sheet (universal cassette)/5.5" x 8.5" to 12" x 18"/17 lb. bond to 140 lb. index 1,500-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 150-sheet bypass/4" x 6" to 12" x 18", 8" x 13"/17 lb. bond to 100 lb. cover or up to 300 gsm |
| Fax Features APER INPUT Reversing Auto Document Feeder Original Size Tray 1 & Tray 2 Tray 3 Tray 4 Bypass Tray LU-204 Large Capacity Unit | Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas Transmission, Password Transmission/Reception, PC-Fax, Polling Transmission/Reception, Priority Transmission, Print Setting or Overnight Reception, Program Dialing (400 programs) Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing 78 opm, Capacity: 100 Sheets, Paper Size: 5.5" x 8.5" to 11" x 17", Paper Weight: Single-sided: 9.25 lb. to 55.75 lb. bond, Double Sided or mixed: 13.25 lb. to 34 lb. bond Up to 11" x 17" 500-sheet (universal cassette)/5.5" x 8.5" to 12" x 18"/17 lb. bond to 140 lb. index 1,500-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index |
| Fax Features APER INPUT Reversing Auto Document Feeder Original Size Tray 1 & Tray 2 Tray 3 Tray 4 Bypass Tray LU-204 Large Capacity Unit LU-301 Large Capacity Unit | Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas Transmission, Password Transmission/Reception, PC-Fax, Polling Transmission/Reception, Print's Transmission, Print Setting or Overnight Reception, Program Dialing (400 programs) Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing 78 opm, Capacity: 100 Sheets, Paper Size: 5.5" x 8.5" to 11" x 17", Paper Weight: Single-sided: 9.25 lb. to 55.75 lb. bond, Double Sided or mixed: 13.25 lb. to 34 lb. bond Up to 11" x 17" 500-sheet (universal cassette)/5.5" x 8.5" to 12" x 18"/17 lb. bond to 140 lb. index 1,500-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1500-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 150-sheet bypass/4" x 6" to 12" x 18", 3" x 13"/17 lb. bond to 140 lb. index 2,500-sheet 8,5" x 11", 8.5" x 13", 17", 12" x 18"/17 lb. bond to 140 lb. index 3,000-sheets/8.5" x 11", 8.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 3,000-sheets/8.5" x 11", 8.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index |
| Fax Features Fax Features Reversing Auto Document Feeder Original Size Tray 1 & Tray 2 Tray 3 Tray 4 Bypass Tray LU-204 Large Capacity Unit LU-301 Large Capacity Unit Maximum Paper Capacity | Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas Transmission, Password Transmission/Reception, PC-Fax, Polling Transmission/Reception, Priority Transmission, Print Setting or Overnight Reception, Program Dialing (400 programs) Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing 78 opm, Capacity: 100 Sheets, Paper Size: 5.5" x 8.5" to 11" x 17", Paper Weight: Single-sided: 9.25 lb. to 55.75 lb. bond, Double Sided or mixed: 13.25 lb. to 34 lb. bond Up to 11" x 17" 500-sheet (universal cassette)/5.5" x 8.5" to 12" x 18"/17 lb. bond to 140 lb. index 1,500-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index |
| Fax Features APER INPUT Reversing Auto Document Feeder Original Size Tray 1 & Tray 2 Tray 3 Tray 4 Bypass Tray LU-204 Large Capacity Unit LU-301 Large Capacity Unit Maximum Paper Capacity | Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas Transmission, Password Transmission/Reception, PC-Fax, Polling Transmission/Reception, Priority Transmission, Print Setting or Overnight Reception, Program Dialing (400 programs, Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing 78 opm, Capacity: 100 Sheets, Paper Size: 5.5" x 8.5" to 11" x 17", Paper Weight: Single-sided: 9.25 lb. to 55.75 lb. bond, Double Sided or mixed: 13.25 lb. to 34 lb. bond Up to 11" x 17" 500-sheet (universal cassette)/5.5" x 8.5" to 12" x 18"/17 lb. bond to 140 lb. index 1,500-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 150-sheet bypass/4" x 6" to 12" x 18", 4" x 6"/17 lb. bond to 100 lb. cover or up to 300 gsm 2,500-sheets/8.5" x 11", 8.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 3,000-sheets/8.5" x 11", 15.5" x 8.5" x 13"/17 lb. bond to 140 lb. index 3,000-sheets/8.5" x 11", 8.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 3,000-sheets/8.5" x 11", 15.5" x 8.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 6,650 sheets (total, with options) |
| Fax Features PAPER INPUT Reversing Auto Document Feeder Original Size Tray 1 & Tray 2 Tray 3 Tray 4 Bypass Tray LU-204 Large Capacity Unit LU-301 Large Capacity Unit Maximum Paper Capacity APPLICATIONS Network & Device Management | Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas Transmission, Password Transmission/Reception, PC-Fax, Polling Transmission/Reception, Priority Transmission, Print Setting or Overnight Reception, Program Dialing (400 programs, Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing 78 opm, Capacity: 100 Sheets, Paper Size: 5.5" x 8.5" to 11" x 17", Paper Weight: Single-sided: 9.25 lb. to 55.75 lb. bond, Double Sided or mixed: 13.25 lb. to 34 lb. bond Up to 11" x 17" 500-sheet (universal cassette)/5.5" x 8.5" to 12" x 18"/17 lb. bond to 140 lb. index 1,500-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 100-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 150-sheet bypass/4" x 6" to 12" x 18"/17 lb. bond to 100 lb. cover or up to 300 gsm 2,500-sheets/8.5" x 11", 8.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 3,000-sheets/8.5" x 11", 8.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 4,650 sheets (total, with options) PageScope Data Administrator, Driver Packaging Utility, HDD Back-Up Utility, Log Management Utility |
| | Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas Transmission, Password Transmission/Reception, PC-Fax, Polling Transmission/Reception, Priority Transmission, Print Setting or Overnight Reception, Program Dialing (400 programs), Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing 78 opm, Capacity: 100 Sheets, Paper Size: 5.5" x 8.5" to 11" x 17", Paper Weight: Single-sided: 9.25 lb. to 55.75 lb. bond, Double Sided or mixed: 13.25 lb. to 34 lb. bond Up to 11" x 17" 500-sheet (universal cassette)/5.5" x 8.5" to 12" x 18"/17 lb. bond to 140 lb. index 1,500-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,50-sheets/8.5" x 11", 8.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 3,000-sheets/8.5" x 11", 15.5" x 8.5" 6,650 sheets (total, with options) |
| Fax Features PAPER INPUT Reversing Auto Document Feeder Original Size Tray 1 & Tray 2 Tray 3 Tray 4 Bypass Tray LU-204 Large Capacity Unit LU-201 Large Capacity Unit Maximum Paper Capacity APPLICATIONS Network & Device Management User Tools | Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas Transmission, Password Transmission/Reception, PC-Fax, Polling Transmission/Reception, Priority Transmission, Print Setting or Overnight Reception, Program Dialing (400 programs) Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing 78 opm, Capacity: 100 Sheets, Paper Size: 5.5" x 8.5" to 11" x 17", Paper Weight: Single-sided: 9.25 lb. to 55.75 lb. bond, Double Sided or mixed: 13.25 lb. to 34 lb. bond Up to 11" x 17" 500-sheet (universal cassette)/5.5" x 8.5" to 12" x 18"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4 x 6"/17 lb. bond to 140 lb. index 2,500-sheets/8.5" x 11", 5.5" x 8.5" x 13"/17 lb. bond to 140 lb. index 3,000-sheets/8.5" x 11", 5.5" x 8.5" x 13"/17 lb. bond to 140 lb. index 3,000-sheets/8.5" x 11", 5.5" x 8.5" x 13"/17 lb. bond to 140 lb. index 3,000-sheets/8.5" x 11", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 3,000-sheets/8.5" x 11", 15.5" x 8.5" PageScope Data Administrator, Driver Packaging Utility, HDD Back-Up Utility, Log Management Utility PageScope Data Administrator, Driver Packaging Utility, HDD Back-Up Utility, Log Management Utility PageScope Veb Connection, PageScope Direct Print, PageScope Box Operator, PageScop |
| Fax Features Fax Features Reversing Auto Document Feeder Original Size Tray 1 & Tray 2 Tray 3 Tray 4 Bypass Tray LU-204 Large Capacity Unit LU-301 Large Capacity Unit Maximum Paper Capacity APPLICATIONS Network & Device Management User Tools Management Tools PageScope Enterprise Suite: | Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas Transmission, Password Transmission/Reception, PC-Fax, Polling Transmission/Reception, Priority Transmission, Print Setting or Overnight Reception, Program Dialing (400 programs), Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing 78 opm, Capacity: 100 Sheets, Paper Size: 5.5" x 8.5" to 11" x 17", Paper Weight: Single-sided: 9.25 lb. to 55.75 lb. bond, Double Sided or mixed: 13.25 lb. to 34 lb. bond Up to 11" x 17" 500-sheet (universal cassette)/5.5" x 8.5" to 12" x 18"/17 lb. bond to 140 lb. index 1,500-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,50-sheets/8.5" x 11", 8.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 3,000-sheets/8.5" x 11", 15.5" x 8.5" 6,650 sheets (total, with options) |
| | Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas Transmission, Password Transmission/Reception, PC-Fax, Polling Transmission/Reception, Priority Transmission, Print Setting or Overnight Reception, Program Dialing (400 programs, Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing 78 opm, Capacity: 100 Sheets, Paper Size: 5.5" x 8.5" to 11" x 17", Paper Weight: Single-sided: 9.25 lb. to 55.75 lb. bond, Double Sided or mixed: 13.25 lb. to 34 lb. bond Up to 11" x 17" 500-sheet (universal cassette)/5.5" x 8.5" to 12" x 18"/17 lb. bond to 140 lb. index 1,500-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 10,000-sheet Size: 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet Mixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (niver acasette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet size to ta 2" x 18", 8" x 13"/17 lb. bond to 140 lb. index 1,650 sheets (total, with options) PageScope Data Administrator, Driver Packaging Utility, HDD Back-Up Utility, Log Management Utility |
| Fax Features PAPER INPUT Reversing Auto Document Feeder Original Size Tray 1 & Tray 2 Tray 3 Tray 4 Bypass Tray LU-204 Large Capacity Unit LU-301 Large Capacity Unit Maximum Paper Capacity APPLICATIONS Network & Device Management User Tools Management Tools PageScope Enterprise Suite: | Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas Transmission, Password Transmission/Reception, PC-Fax, Polling Transmission/Reception, Priority Transmission, Print Setting or Overnight Reception, Program Dialing (400 programs, Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing 78 opm, Capacity: 100 Sheets, Paper Size: 5.5" x 8.5" to 11" x 17", Paper Weight: Single-sided: 9.25 lb. to 55.75 lb. bond, Double Sided or mixed: 13.25 lb. to 34 lb. bond Up to 11" x 17" 500-sheet (universal cassette)/5.5" x 8.5" to 12" x 18"/17 lb. bond to 140 lb. index 1,500-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1500-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 1", 12" x 18"/17 lb. bond to 140 lb. index 3,000-sheets/8.5" x 11", 1", 12" x 18"/17 lb. bond to 140 lb. index 6,650 sheets (total, with options) PageScope Data Administrator, Driver Packaging Utility, HDD Back-Up Utility, Log Management Utility PageScope Web Connection, PageScope Direct Print, PageScope Box Operator, PageScope Print Status Notifier, Font Management Utility, Copy Protect Utility, Print Utility for Unix bizhub vCare support PageScope Account Manager, PageScope Authentication Manager, PageScope MyPanel Manager, PageScope Net Care Device Manager (standard) AU-102 B |
| Fax Features PAPER INPUT Reversing Auto Document Feeder Original Size Tray 1 & Tray 2 Tray 3 Tray 4 Bypass Tray LU-204 Large Capacity Unit Auto-204 Large Capacity Unit Maximum Paper Capacity Unit Maximum Paper Capacity Unit Maximum Paper Capacity APPLICATIONS Network & Device Management User Tools Management Tools PageScope Enterprise Suite: ADDITIONAL OPTIONS Authentication Devices | Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas Transmission, Password Transmission/Reception, PC-Fax, Polling Transmission/Reception, Priority Transmission, Print Setting or Overnight Reception, Program Dialing (400 programs) Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission/Reception, Priority Transmission, Print Setting or Overnight Reception, Program Dialing (400 programs) Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing 78 opm, Capacity: 100 Sheets, Paper Size: 5.5" x 8.5" to 11" x 17", Paper Weight: Single-sided: 9.25 lb. to 55.75 lb. bond, Double Sided or mixed: 13.25 lb. to 34 lb. bond Up to 11" x 17" 500-sheet (inversal cassette)/5.5" x 8.5" to 12" x 18"/17 lb. bond to 140 lb. index 1,500-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,600-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,600-sheet (bypass/4" x 6" to 12" x 18", 3" x 13"/17 lb. bond to 100 lb. cover or up to 300 gsm 2,500-sheets/8.5" x 11", 15.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 3,000-sheets/8.5" x 11", 17.1" x 18"/17 lb. bond to 140 lb. index 6,650 sheets / 8.5" x 11", 17.1" x 18"/17 lb. bond to 140 lb. index 6,650 sheets / 8.5" x 11", 17.1" x 18"/17 lb. bond to 140 lb. index 6,650 sheets / 8.5" x 11", 20 yr Reception, PageScope Direct Print, PageScope Box Operator, PageScope Print Status Notifier, Font Management Utility, Copy Protect Utility, Print Utility for Unix bizhub vCare support PageScope Account Manager, PageScope Authentication Manager, PageScope MyPrint Manager, PageScope MyPanel Manager, PageScope Net Care Device Manager (standard) AU-102 Biometric Authentication Unit, AU-201H HI |
| | Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas Transmission, Password Transmission/Reception, PC-Fax, Polling Transmission/Reception, Priority Transmission, Print Setting or Overnight Reception, Program Dialing (400 programs Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing 78 opm, Capacity: 100 Sheets, Paper Size: 5.5" x 8.5" to 11" x 17", Paper Weight: Single-sided: 9.25 lb. to 55.75 lb. bond, Double Sided or mixed: 13.25 lb. to 34 lb. bond Up to 11" x 17" 500-sheet (universal cassette)/5.5" x 8.5" to 12" x 18"/17 lb. bond to 140 lb. index 1,500-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 150-sheet (bypass/4" x 6" to 12" x 18", 8" x 13"/17 lb. bond to 100 lb. cover or up to 300 gsm 2,500-sheets/8.5" x 11", 8.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 6,650 sheets (total, with options) PageScope Data Administrator, Driver Packaging Utility, HDD Back-Up Utility, Log Management Utility PageScope Account Manager, PageScope Direct Print, PageScope Box Operator, PageScope Print Status Notifier, Font Management Utility, Copy Protect Utility, Print Utility for Unix Dizhub VCare support PageScope Account Manager, PageScope Authentication Manager, PageScope MyPrint Manager, PageScope MyPanel Manager, PageScope Net Care Device Manager (standard) AU-102 Biometric Authentication Unit, AU-201H HID Card Authentication Unit, AU-202H HID IClass Card Authentication Unit, AU-204H Magnetic Stripe Card Reader, AU-211P CAC/PIV Solution", SC-507 Copy Guard Kit, WT-506 Working Table to support Authentication Devices KH-101 Keyboard Mount Kit for External Keyboard, EK-604 USB Interface for External Keyboard and Bluetooth Support |
| | Exposure Mode, Group Dialing (up to 500 one-touche's per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas Transmission, Password Transmission/Reception, PC-Fax, Polling Transmission/Reception, Priority Transmission, Priority Transmission/Reception, Program Dialing (400 programs Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing 78 opm, Capacity: 100 Sheets, Paper Size: 5.5" x 8.5" to 11" x 17", Paper Weight: Single-sided: 9.25 lb. to 55.75 lb. bond, Double Sided or mixed: 13.25 lb. to 34 lb. bond Up to 11" x 17" 500-sheet (inviersal cassette)/5.5" x 8.5" to 12" x 18"/17 lb. bond to 140 lb. index 1,500-sheet (fixed cassette)/6.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 1" x 17", 1" x 16", 1" x 17", 1" x 16", 11" x 17", 1" x 17", 1 |
| | Exposure Mode, Group Dialing (up to 500 one-touche's per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas Transmission, Password Transmission, Peception, PC-Fax, Polling Transmission/Reception, Priority Transmission/Reception, Priority Transmission/Reception, Program Dialing (400 programs Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing 78 opm, Capacity: 100 Sheets, Paper Size: 5.5" x 8.5" to 11" x 17", Paper Weight: Single-sided: 9.25 lb. to 55.75 lb. bond, Double Sided or mixed: 13.25 lb. to 34 lb. bond Up to 11" x 17" 500-sheet (niversal cassette)/5.5" x 8.5" to 12" x 18"/17 lb. bond to 140 lb. index 1,500-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,500-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,500-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 7.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 3,000-sheets/8.5" x 11", 4.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 3,000-sheets/8.5" x 11", 6.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 6,650 sheets (total, with options) PageScope Data Administrator, Driver Packaging Utility, HDD Back-Up Utility, Log Management Utility PageScope Net Care Device Manager (standard) AU-102 Biometric Authentication Unit, AU-201H HID Card Authentication Unit, AU-202H HID iClass Card Authentication Unit, AU-204H Magnetic Stripe Card Reader, AU-211P CAC/PIV Solution", SC-507 Copy Guard Kit, WT-506 Working Table to support Authentication Unit, AU-204H Magnetic Stripe Card Reader, AU-211P CAC/PIV Solution", SC-507 Copy Guard Kit, WT-506 Working Table to support Authentication Devices KH-101 Keyboard, EK-604 USB Interface for External Keyboard, BK-605 USB |
| | Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas Transmission, Password Transmission/Reception, PC-Fax, Polling Transmission/Reception, Priority Transmission, Print Setting or Overnight Reception, Program Dialing (400 programs Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing 78 opm, Capacity: 100 Sheets, Paper Size: 5.5" x 8.5" to 11" x 17", Paper Weight: Single-sided: 9.25 lb. to 55.75 lb. bond, Double Sided or mixed: 13.25 lb. to 34 lb. bond Up to 11" x 17" 500-sheet (inversal cassette)/5.5" x 8.5" to 12" x 18"/17 lb. bond to 140 lb. index 1,500-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 3,000-sheets/8.5" x 11", 8.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 6,650 sheets (total, with options) PageScope Data Administrator, Driver Packaging Utility, HDD Back-Up Utility, Log Management Utility PageScope Web Connection, PageScope Direct Print, PageScope Box Operator, PageScope Print Status Notifier, Font Management Utility, Copy Protect Utility, Print Utility for Unix bizhub vCare support PageScope Account Manager, PageScope Authentication Manager, PageScope MyPanel Manager, PageScope Net Care Device Manager (standard) AU-102 Biometric Authentication Unit, AU-201H HID Card Authentication Unit, AU-202H HID IClass Card Authentication Unit, AU-204H Magnetic Stripe Card Reader, AU-211P CAC/PIV Solution*, SC-507 Copy Guard Kit, WT-506 Working Table to support Authentication Devices KH-101 Keyboard Mount Kit for External Keyboard, EK-604 USB Inte |
| | Exposure Mode, Group Dialing (up to 500 one-touche's per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas Transmission, Password Transmission, Peception, PC-Fax, Polling Transmission/Reception, Priority Transmission/Reception, Priority Transmission/Reception, Program Dialing (400 programs Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing 78 opm, Capacity: 100 Sheets, Paper Size: 5.5" x 8.5" to 11" x 17", Paper Weight: Single-sided: 9.25 lb. to 55.75 lb. bond, Double Sided or mixed: 13.25 lb. to 34 lb. bond Up to 11" x 17" 500-sheet (niversal cassette)/5.5" x 8.5" to 12" x 18"/17 lb. bond to 140 lb. index 1,500-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,500-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,500-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 7.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 3,000-sheets/8.5" x 11", 4.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 3,000-sheets/8.5" x 11", 6.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 6,650 sheets (total, with options) PageScope Data Administrator, Driver Packaging Utility, HDD Back-Up Utility, Log Management Utility PageScope Net Care Device Manager (standard) AU-102 Biometric Authentication Unit, AU-201H HID Card Authentication Unit, AU-202H HID iClass Card Authentication Unit, AU-204H Magnetic Stripe Card Reader, AU-211P CAC/PIV Solution", SC-507 Copy Guard Kit, WT-506 Working Table to support Authentication Unit, AU-204H Magnetic Stripe Card Reader, AU-211P CAC/PIV Solution", SC-507 Copy Guard Kit, WT-506 Working Table to support Authentication Devices KH-101 Keyboard, EK-604 USB Interface for External Keyboard, BK-605 USB |
| | Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Nailbox Transmission/Reception, Program Dialing (400 programs Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing 78 opm, Capacity: 100 Sheets, Paper Size: 5.5" x 8.5" to 11" x 17", Paper Weight: Single-sided: 9.25 lb. to 55.75 lb. bond, Double Sided or mixed: 13.25 lb. to 34 lb. bond Up to 11" x 17" 500-sheet (iniversal cassette)/5.5" x 8.5" to 12" x 18"/17 lb. bond to 140 lb. index 1.000-sheet (iniversal cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1.000-sheet (iniversal cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1.000-sheet (iniversal cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1.000-sheet (iniver cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1.000-sheet (iniver cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1.000-sheet (iniver cassette)/8.5" x 11", 5.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1.000-sheet (iniver cassette)/8.5" x 11", 1.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 1.000-sheet (bypass/4" x 6" to 12" x 18", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 3.000-sheet/8.5" x 11", 8.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 3.000-sheet/8.5" x 11", 6.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 3.000-sheet/8.5" x 11", 6.5" x 6.5" x 10", 7.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 3.000-sheet/8.5" x 11", 6.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 3.000-sheet/8.5" x 11", 15.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 3.000-sheet/8.5" x 11", 15.5" x 8.5", 4" x 6"/17 lb. bond to 140 lb. index 3.000-sheet/9.5" x 10", 2000 perfect Print, PageScope Box Operator, PageScope Print Status Notifier, Font Management Utility, Copy Protect Utility, Print Utility for Unix birbub Ccare support PageScope Data Administrator, Drive Packaging Utili |
| | Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Memory/Quick Dial, Overseas Transmission, Password Transmission/Reception, PC-Fax, Polling Transmission/Reception, Priority Transmission, Print Setting or Overnight Reception, Program Dialing (400 programs Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing 78 opm, Capacity: 100 Sheets, Paper Size: 5.5" x 8.5" to 11" x 17", Paper Weight: Single-sided: 9.25 lb. to 55.75 lb. bond, Double Sided or mixed: 13.25 lb. to 34 lb. bond Up to 11" x 17" 500-sheet (inved cassette)/8.5" x 11", 5.5" x 8.5", 4" 80"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" 80"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" 80"/17 lb. bond to 140 lb. index 1,000-sheet Size 1, 5.5" x 11", 8.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 1,000-sheet Size 1, 5.5" x 11", 8.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 1,000-sheet Size 1, 5.5" x 11", 8.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 1,000-sheet Size 1, 5.5" x 11", 8.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 1,000-sheet Size 1, 5.5" x 11", 8.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 6,650 sheets (total, with options) PageScope Data Administrator, Driver Packaging Utility, HDD Back-Up Utility, Log Management Utility PageScope Web Connection, PageScope Direct Print, PageScope Box Operator, PageScope Print Status Notifier, Font Manager, PageScope Net Care Device Manager (standard) AU-102 Biometric Authentication Unit, AU-201H HID Card Authentication Unit, AU-202H HID Class Card Authentication Unit, AU-204H Magnetic Stripe Card Reader, AU-211P CAC/PN Solution", SC-507 Copy Guard Kit, WT-506 Working Table to support Authentication Dirt, AU-204H Magnetic Stripe Card Reader, AU-211P CAC/PN Solution", SC-507 Copy Guard Kit, WT-506 Working Table to support A |
| | Exposure Mode, Group Dialing (up to 500 one-fouches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Persynthesion/Reception, Persynthesion, Persynthesion/Reception, Persynthesion/Reception, Persynthesion, Persynthesin, Pe |
| | Exposure Mode, Group Dialing (up to 500 one-touches per group), Image Rotation Transmission/Reception, Mailbox Transmission/Reception, Nemory/Ouick Dial, Overseas Transmission, Password Transmission/Reception, PC-Fax, Polling Transmission/Reception, Priority Transmission, Print Setting or Overnight Reception, Program Dialing (400 programs Redial, Relay Broadcasting, Relay Transmission, Remote Reception, Timer Transmission, TSI Routing 78 opm, Capacity: 100 Sheets, Paper Size: 5.5" x 8.5" to 11" x 17", Paper Weight: Single-sided: 9.25 lb. to 55.75 lb. bond, Double Sided or mixed: 13.25 lb. to 34 lb. bond Up to 11" x 17" 500-sheet (inved cassette)/8.5" x 11", 5.5" x 8.5", 4" 80"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" 80"/17 lb. bond to 140 lb. index 1,000-sheet (fixed cassette)/8.5" x 11", 5.5" x 8.5", 4" 80"/17 lb. bond to 140 lb. index 1,000-sheet Size 1, 5.5" x 11", 8.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 1,000-sheet Size 1, 5.5" x 11", 8.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 1,000-sheet Size 1, 5.5" x 11", 8.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 1,000-sheet Size 1, 5.5" x 11", 8.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 1,000-sheet Size 1, 5.5" x 11", 8.5" x 14", 11" x 17", 12" x 18"/17 lb. bond to 140 lb. index 6,650 sheets (total, with options) PageScope Data Administrator, Driver Packaging Utility, HDD Back-Up Utility, Log Management Utility PageScope Web Connection, PageScope Direct Print, PageScope Box Operator, PageScope Print Status Notifier, Font Manager, PageScope Net Care Device Manager (standard) AU-102 Biometric Authentication Unit, AU-201H HID Card Authentication Unit, AU-202H HID Class Card Authentication Unit, AU-204H Magnetic Stripe Card Reader, AU-211P CAC/PN Solution", SC-507 Copy Guard Kit, WT-506 Working Table to support Authentication Dirt, AU-204H Magnetic Stripe Card Reader, AU-211P CAC/PN Solution", SC-507 Copy Guard Kit, WT-506 Working Table to support A |



Konica Minolta Optimized Print Services offers a full suite of device output services and workflow solutions that increase efficiency and control costs. Please contact your authorized Konica Minolta sales representative for details.

KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive Ramsey, NJ 07446

www.CountOnKonicaMinolta.com www.kmbs.konicaminolta.us

© 2011 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Konica Minolta is a registered trademark of KONICA MINOLTA HOLDINGS, INC. bizhub, Emperon, and PageScope are trademarks of KONICA MINOLTA BUSINESS TechNOLOGIES, INC. Simitri is a registered trademark of KONICA MINOLTA BUSINESS SOLUTIONS. All other brands and product names are registered trademarks of their respective owners. Design & specifications are subject to change without notice. Some functions may require options, which may or may not be available at time of launch.







ABBYY